

COMPARE/CONTRAST 22000 SERIES RING & BUSHINGS WITH BARRY-BOND MOUNTS

<u>PRODUCT FEATURES</u>	<u>22000 SERIES MOUNTS</u>	<u>BARRY-BOND MOUNTS</u>
DESIGN	2 pc - bonded tube/ring	1 pc - bonded tube
FITS SUPPORT PLATE THICKNESS	See Attached	See Attached
FITS MOUNTING HOLE DIAMETER	See Attached	See Attached
AXIAL LOAD RANGE	40-4560 lbs.	75-2100 lbs.
NATURAL FREQUENCY	10-20 Hz.	10-20 Hz.
RESILIENT ELEMENT	Neoprene	Natural Rubber
OPERATING TEMPERATURE RANGE	-20F to +180F	-20F to +180F
RESISTANCE TO OILS & OZONE	High	Medium
3HT	1.5 oz. to 2 lbs. 14 oz.	0.3 oz. to 13.8 oz.
REBOUND PROTECTION	High	Medium
MULTI-DIRECTIONAL SHOCK PROTECTION	High	Medium
PROVIDES NOISE ATTENUATION	Yes	Yes
FAILSAFE WHEN USED W/BOLT & WASHERS	Yes	Yes
DURABILITY	High	Medium
EASE OF INSTALLATION	Medium	High
POTENTIAL FOR VISABLE "GAP" WHEN IN COMPRESSION	Yes	No
COST/PRICE	Medium	LOW

22000 SERIES

<i>PART NUMBER</i>	<i>PLATE THICKNESS</i>	<i>MOUNTING HOLE DIAMETER</i>	<i>BOLT SIZE</i>
22001	.375	.75	3/8
22002	.563	1.25	1/2
22003	.875	1.5	5/8
22004	1.125	2.25	7/8
22005	1.25	2.5	1.0

BARRY BONDS

<i>TYPE NUMBER</i>	<i>PLATE THICKNESS</i>	<i>MOUNTING HOLE DIAMETER</i>	<i>BOLT SIZE</i>
BC-1120-1	.31	.75	3/8
BC-1120-3	.31	.75	3/8
BC-1121-2	.38	1.12	1/2
BC-1121-4	.38	1.12	1/2
BC-1122-2	.62	1.25	1/2
BC-1122-4	.62	1.25	1/2
BC-1123-2	.75	1.50	5/8
BC-1123-5	.75	1.50	5/8
BC-1124-2	.93	1.81	5/8
BC-1124-5	.93	1.81	5/8
BC-1125-2	.75	2.00	3/4
BC-1125-4	.75	2.00	3/4